

# Why Choose AEI

## Tool-Less Maintenance & Labor Saving Installation



AEI provides mounting solutions that are safe, fast to install and the labor saving devices actually pay for themselves many times over vs. ordinary chain or standard options that are not engineered for the application. The end result whether it's dozens or thousands will be fixtures that are plumb, square and that don't sway or tilt with air movement. AEI has the cleanest mounting options for new construction or retrofit installations and the shortest lead times in the industry!

### Tool-Less Maintenance

- Patented Push Button Access
- 1/4 Turn Tool-Less Wireway Access
- Steel Fixture Tool-Less Wireway Access

### Labor Saving Installation

- Slide Box System
- Single Point System
- Gripper System
- Factory Installed Access Plates
- Factory Installed cord & plugs
- Factory Installed Lamps
- Factory Installed Sensors
- Factory Peeled Reflectors
- Lightweight Aluminum Housings
- Disconnects & Switches

## Tool-Less Maintenance

Standard Floor Side Access On Most AEI Fixtures!

### Patented "Push Button" Access



**Step 1.**  
Locate buttons at each end of fixture and press to release the center assembly.



**Step 2.**  
Lower the center wire way assembly until it rests approximately at a 90 degree angle.



**Step 3.**  
In just seconds you now have complete access to the AEI fixture wireway without having to remove the lamps.

### 1/4-Turn Tool-Less Wireway Access



**Step 1.**  
While the fixture is hanging remove the center lamps only and locate the two 1/4-turn fasteners securing the wireway access reflector.



**Step 2.**  
Turn each 1/4-turn 90 degrees. Then lift the wireway reflector up and remove it.



**Step 3.**  
By removing just the one wireway reflector you now have complete access to the ballast channel for easy maintenance or replacement. Simply reverse the steps to put the fixture back together.

### Steel Fixture Tool-Less Wireway Access



**Step 1.**  
While the fixture is hanging remove the center lamps only and locate the wireway ballast cover.



**Step 2.**  
With a hand at each end of the ballast cover simply pinch one side and remove the cover.



**Step 3.**  
By removing just the one wireway cover you now have complete access to the ballast channel for easy maintenance or replacement. Simply reverse the steps to put the fixture back together.